INDION CX105 RES

(Monitor/transmitter/controller)

Our CX105 is an isolated output 4-20mA industrial transmitter for reading contacting Resistivity. sensors. Easily power the unit with available two-wire power supply loop. Ideal for connecting to a PLC for advanced control systems. Versatile mounting options for wall or panel mount. With a dual display LCD, monitoring both the measuring value and the temperature is simple.The CX105 is CE certified.



FG code : ZNC07GUTNA00000
Model no: CX105 RES

Additional Key Features:

1. Large LCD screen for easy reading
2. Isolated 4-20 mA analog output
3. Automatic temperature compensation.
4. Flexible mounting options

Technical Specifications:

Transmitter/Monitor/Controller	Panel Mounted / Field Mounted
Measuring Range (Resistivity)	1 KΩ·cm to 18.3 MΩ·cm
Accuracy	+/- 0.5% of reading.
Repeatability	+/-0.05% of span.
Compensation Temperature Sensor	Automatic, PT1000 RTD
Operating Temperature	-10 ˚c to 70˚c (14 ˚F to 158 ˚F) ; 0-95% relative humidity, non - condensing
Temperature Drift	Zero and Span : +/-0.02% of span per ˚c
Conductivity Calibration	1 POINT
Outputs	
Current Output	Isolated 4 – 20 Ma output with 0.004 Ma (12-Bit) resolution update rate : 1 second Max loop impedance : 250Ω at 24v; 600Ω at 31c ; 1500Ω at 48v
Electrical data	
Memory	Non – volatile ; all user setting are retained indefinitely without battery backup
Input Power Supply	19-48 VDC , regulated , 30mA max
Display	
LCD	128*65 dot matrix, figure or alphabet: 12x8, 28x15, 32x18, etc.....
Contrast	User selected , 5 level
Materials	
IP Rating	IP65
Mechanical Specifications	
Dimensions (H x W x D)	HWD (92×92×35)mm
Weight	0.84 lbs (381 g).

For more information write to us at: inst.soles@ionexchonge.co.in

To the best of our knowledge the information contained in this publication is accurate. Ion Exchange (India) Ltd. maintains a policy of continuous development and reserves the right to amend the information given herein without notice.
INDION Is the registered trademark of ION EXCHANGE (India) Ltd.

Corporate Office
Ion House, Dr. E. Moses Road,
Mahalaxmi, Mumbai 400 011
Tel: +91 22 3989 0909
Fax: +91 22 2493 8737
E-mail: ieil@ionexchange.co.in

Sales Office
Ion House, No. C-72 & 83, Devasandra Industrial Area,
ITI Ancillary Industrial Estate, ITPL Whitefield Road,
Mahadevapura Post,Bengaluru 500 048
Tel: -ï-91 80 220 428 88
E-mail: bnghocroser@ionexchange.co.in

Factory
105, SIPCOT Industrial Complex,
SIPCOT, Hosur, Tamil Nadu
Tel: +91 4344 304 600
E-mail: inst.production@ionexchOnge.co.in